MMCOMBI-W Thermometer in White Case

COST EFFECTIVE SOLUTION TO HIGH ACCURACY MEASUREMENT

Two best selling products from TM Electronics - the MM2000 Thermometer and the TP05 needle probe are now combined in one unit.

The MMCOMBI-W is an easy to use handheld thermometer, which is ideal for a wide range of applications – particularly repeat temperature recordings where accuracy and speed are important. The integral sensor is a general purpose needle probe for use wherever penetration of semi-solid product is required – eg cooked/chilled foods.

ADVANTAGES

High accuracy Splash-proof Simple point-and-probe action No trailing wires No plug-in connection Battery powered Food-safe

THERMOMETER FEATURES

- White Splash-proof case
- 'C/'F selectable
- Very high accuracy ± 0.2°C ±0.15% of reading
- Wide operating range -30 to 50°C
- 2 year warranty
- Microprocessor driven
- Ergonomic and robust case
- Excellent long term stability
- Conforms to food hygiene regulations for 0.5°C accuracy between 0°C and 5°C

PROBE FEATURES

- Waterproof assembly
- · Encapsulated solid handles
- High accuracy +/- 0.25°C (type T)
- Food grade stainless steel
- 1m length cable

SYSTEM FEATURES

- System Accuracy of ±0.5°C over critical food temperature range
- · Cost effective solution for compliance with HACCP

ACCESSORIES

- Probe Wipes
- Temperature record book
- Wall mount holder

SPECIFICATION

For MMCOMBI-W Thermometer

Environmental

AMBIENT OPERATING RANGE : $-30 \text{ to } 50 \,^{\circ}\text{C}$ STORAGE TEMPERATURE RANGE : $-40 \text{ to } 50 \,^{\circ}\text{C}$ HUMIDITY : 0 to 70% R.H.

Electrical

SENSOR TYPE : T

MEASUREMENT RANGE : -100 to 400°C

ACCURACY @ 23 °C : ± 0.2 °C ± 0.15 % of reading

COLD JUNCTION COMPENSATION : 0.075°C/°C CHARACTERISIC ERRORS : Less than 0.05°C TEMPERATURE COEFFICIENT : 0.01% of reading /°C

RESOLUTION : 0.1° to 1° above 1000° (auto ranging)

General

BATTERY : PP3 9V I.E.C. 6F22

BATTERY LIFE (INTERMITTENT USE) : GREATER THAN 200 HOURS (ALKALINE)

WEIGHT : 155 gms

DIMENSIONS : 130 X 70 X 33 mm

ORDER CODE MMCOMBI-W