DATA SHEET

QUICK CONNECT TYPE 'T' AIR PROBE

QCTA-V

General Purpose Probe available in Various Diameter and Lengths

Description

Terminated using a moulded terminal block with screws for quick connection to sensor wire.

Construction

Minerally Insulated Stainless Steel Probe Food Grade 316 Stainless Steel Waterproof High Temperature Polypropylene Terminal Block

Available diameters: 1.5mm, 3mm, 4mm, 5mm and 6mm

Available lengths: 100mm, 300mm and 1,000mm

Sensor Features

> TOTAL ENCAPSULATION TECHNIQUE FOR MAXIMUM STRENGTH AND DURABILITY.

Offering high resistance to excess heat and greater protection from damage

> WATERPROOF TERMINAL BLOCK

Probe is completely waterproof

> HIGH TEMPERATURE POLYPROPYLENE TERMINAL BLOCK

Fitted with screws for quick connection to sensor wire

> HIGH ACCURACY THERMOCOUPLE MATERIAL THROUGHOUT

Type 'T' Thermocouple : $\frac{1}{2}$ Class I (±0.25°C ±0.15%)

\triangleright	WIDE AMBIENT	TEMPERATURE SPECIFICATION	: -30 TO 50 °C
\triangleright	TIME RESPONSE	(96% of value in water)	• 1 0 Secs

> TIME RESPONSE(96% of value in water): 1.0 Secs> MEASUREMENT RANGE: -200 TO 400 °C

57-0346-04 V2